

- Good VSWR
- Indoor application
- Compact volume
- Easy mounting
- Light weight
- ROHS compliant



Technical Data:

Channels	GSM900	DCS	DECT	UMTS2100	WLAN
Frequency Range(MHz)	890~960	1710~1785&1805~1870	1880~1900	1920~1980&2110~2170	2400~2500
Band Width(MHz)	70	75/65	20	60/60	100
Insertion Loss(dB)	≤2.0	≤2.0	≤2.0	≤2.0	≤2.0
Stop-band Attenuation(dB)	≥60@1710~2500 MHz	≥60@890~960MHz ≥60@1880~2500MHz	≥60@890~1870MHz ≥60@1920~2500MHz	≥60@890~1900 MHz ≥60@2400~2500MHz	≥60@890~2170
Isolation(dB)	≥60@1710~2500 MHz	≥60@890~960MHz ≥60@1880~2500MHz	≥60@890~1870MHz ≥60@1920~2500MHz	≥60@890~1900 MHz ≥60@2400~2500MHz	≥60@890~2170
Return Loss(dB)	≥18	≥18	≥18	≥18	≥18
Impedance(Ω)	50				
Connector	N-F				
Input Power (W)	10				
Temperature(℃)	-10~+70				
Size(mm)	482.6×407.7×88.1				
Weight(kg)	8.21				

Dimension:

