

JCDUP-8031C

技术规格书

- 1、产品型号： JCDUP-8031C
- 2、产品名称： GSM&DCS&3G&WLAN 四路合路器
- 3、技术指标：

通道	GSM	DCS	3G	WLAN
频率范围(MHz)	880~960	1710~1880	1920~2170	2400~2500
工作带宽(MHz)	80	170	250	100
插入损耗(dB)	≤0.3	≤0.7	≤0.7	≤0.6
带内波动(dB)	≤0.2	≤0.5	≤0.5	≤0.4
带外抑制(dB)	≥80@CH2	≥80@CH1	≥80@CH1	≥80@CH3
	≥80@CH3	≥80@CH3	≥80@CH2	≥80@CH2
	≥80@CH4	≥80@CH4	≥80@CH4	≥80@CH1
端口隔离(dB)	≥80@CH2	≥80@CH1	≥80@CH1	≥80@CH3
	≥80@CH3	≥80@CH3	≥80@CH2	≥80@CH2
	≥80@CH4	≥80@CH4	≥80@CH4	≥80@CH1
回波损耗(dB)	≥20			
阻抗(Ω)	50			
三阶互调(dBc)	≤-140@+43dBm×2			
接口类型	N-F			
功率容量(W)	100			
工作温度(°C)	-25~+65			
外形尺寸(mm)	229×160×64			
重量(kg)	3.55			

- 4、外形图：

