

JCDUP-8033

技术规格书

- 1、产品型号： JCDUP-8033
- 2、产品名称： 四路合路器
- 3、技术指标：

通道	CH1	CH2	CH3	CH4
频率范围(MHz)	771~779	785~793	799~807	813~821
工作带宽(MHz)	8	8	8	8
插入损耗(dB)	≤1.6	≤1.6	≤1.6	≤1.6
带内波动(dB)	≤0.8	≤0.8	≤0.8	≤0.8
带外抑制(dB)	≥50@CH2 ≥50@CH3 ≥50@CH4	≥50@CH1 ≥50@CH3 ≥50@CH4	≥50@CH1 ≥50@CH2 ≥50@CH4	≥50@CH3 ≥50@CH2 ≥50@CH1
端口隔离(dB)	≥50@CH2 ≥50@CH3 ≥50@CH4	≥50@CH1 ≥50@CH3 ≥50@CH4	≥50@CH1 ≥50@CH2 ≥50@CH4	≥50@CH3 ≥50@CH2 ≥50@CH1
回波损耗(dB)	≥20			
阻抗(Ω)	50			
三阶互调(dBc)	≤-140@+43dBm×2			
接口类型	N-F			
功率容量(W)	100			
工作温度(°C)	-25~+65			
外形尺寸(mm)	209×138×100			
重量(kg)	3.79			

- 4、外形图：

